
QSFP28 LR4 10km



The TQS-HG10-31DCR is a parallel 100Gbps Quad Small Form-factor Pluggable (QSFP) optical module. It provides increased port density and total system cost savings. The QSFP28 full-duplex optical module offers 4 independent transmit and receive channels, each capable of 25.78125Gbps operation for an aggregate data rate of 100Gbps over 10km of single mode fiber.

An optical fiber cable with duplex LC connectors can be plugged into the QSFP28 module receptacle.

The module operates by a single +3.3V power supply. LVCMOS/LVTTL global control signals, such as Module Present, Reset, Interrupt and Low Power Mode, are available with the modules. A 2-wire serial interface is available to send and receive more complex control signals, and to receive digital diagnostic information.

The TQS-HG10-31DCR is designed with form factor, optical/electrical connection and digital diagnostic interface according to the QSFP Multi-Source Agreement (SFF-8436). It has been designed to meet the harshest external operating conditions including temperature, humidity and EMI interference. The module offers very high functionality and feature integration, accessible via a two-wire serial interface.

More Details?[DS180009?](#)

Part No.	Data Rate	Laser	Fiber Type	Distance ^{*Note1}	Op Int
TQS-HG10-31DCR	100Gbps	DFB-based LAN-WDM	SMF	10km	

Product Features

- 4 independent LAN-WDM channels
- Up to 25.78125Gbps data rate per channel
- Duplex LC receptacles
- Hot-pluggable QSFP28 form factor
- Digital diagnostic capabilities
- Maximum link length of 10km on Single Mode Fiber(SMF)

-
- Single +3.3V power supply
 - Operating case temperature: 0~70°
 - Low power consumption < 3.5W
 - RoHS-6 compliant

Compliant Standard

- 100GBASE LR4 100G Ethernet

Product link : <https://www.trixontech.com/qsfp28-lr4-tqs-hg10-31dcr.html>